

## LZ-3AR Refractory Shotcrete Machine



地址 ADD: 郑州市中原区西流湖街道办事处铁炉村西四环东 邮编 P.C.:450042  
Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,  
Zhongyuan District, Zhengzhou, Henan

网址 (Web) : [www.leadcrete.com](http://www.leadcrete.com) E-Mail: [sales@leadcrete.com](mailto:sales@leadcrete.com)

电话 TEL.: +86-371-63902781 传真 FAX: +86-371-63526676

---

## Description

LZ-3AR Refractory Guniting Machine is specifically designed for refractory dry-mix shotcrete gunning applications with air motor drive. With this LZ-3AR, you can get low dust, low bound and high performance spraying flow in nozzle.

## Application

It can be used for refractory spraying applications, as well as for concrete shotcrete application.

LZ-3AR Refractory Guniting Machine is widely used for spraying refractory materials, castable in steel plant. Equipped with ABB frequency converter could achieve variable output from 1m<sup>3</sup>/h to 3m<sup>3</sup>/h.

## Features

1. Variable Output. 5 cylinders piston air motor drive
2. Bag cutter and flat hopper with vibrator
3. Collect dust bag
4. Clean dust gun
5. Heavy-duty solid wheels
6. Coupling and clamp
7. Light weight nozzle
8. Blast rubber hose

地址 ADD: 郑州市中原区西流湖街道办事处铁炉村西四环东 邮编 P.C.:450042  
Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,  
Zhongyuan District, Zhengzhou, Henan

网址 (Web) :[www.leadcrete.com](http://www.leadcrete.com) E-Mail: [sales@leadcrete.com](mailto:sales@leadcrete.com)

电话 TEL.:+86-371-63902781 传真 FAX:+86-371-63526676

## Technical Data

Rated Output	1-3m <sup>3</sup> /h (2-6 ton/h)
Max. Horizontal Conveying Distance	200m
Max. Aggregate Size	Φ10 mm
Conveying Hose Inner Diameter	38mm
Operating air Pressure	0.2-0.4MPa(29-58PSI)
Air Consumption	10-11m <sup>3</sup> /min
Engine	4kw
Material Charging Height	1.1m
Rotor Speed	13.2r/min
Overall Dimension(LxWxH)	1.13x0.54x1.1m
Weight	430kg

Zhengzhou Lead Equipment Co., Ltd.

Add: Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,  
Zhongyuan District, Zhengzhou, Henan

Web:<http://www.leadcrete.com> E-Mail: [sales@leadcrete.com](mailto:sales@leadcrete.com)

TEL: +86-371-63902781 FAX:+86-371-63526676