

LD2000 Concrete Foaming Machine



Description:

On the basis of taking advance of the principle of the structure from advanced facility abroad and seek the user's advice widely. According to China's actual situation, rely on our rich experience in design and manufacturing the hydraulic equipment, we take the innovation and have a distinct personality characteristics as well as completely independent intellectual property rights.

The use of double cylinder hydraulic pump water bodies Push mud, exports of high pressure, can meet the needs of high-rise ratio of the various ingredients used in automatic control, The density foam cement adjust easily selected using the homemade quality matching components, reliable guaranteed after-sales service can use the high-quality home-foaming agent, lower construction cost with running.

Round and Universal Wheels, Mobile and place convenient and flexible.

Application:

- 1.Cast-in-situ wall
- 2.External wall thermal insulation
- 3.Thermal insulation roofing
- 4.Thermal flooring
- 5.Upstanding beam foundation ditches filling
- 6.Sound insulation and fire protection walls
- 7.Playground and track construction
- 8.Sound insulation layer, tunnel lining filling
- 9.Cellar, basement and arch filling



郑州佰利得机器制造有限公司

Zhengzhou Lead Equipment Co., Ltd.

地址 ADD: 郑州市中原区西流湖街道办事处铁炉村西四环东 邮编 P.C.:450042
Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,
Zhongyuan District, Zhengzhou, Henan

网址 (Web) :<http://www.leadcrete.com> E-Mail: sales@leadcrete.com

电话 TEL : +86-371-63902781 传真 FAX: +86-371-63526676

- 10.Sewers and Drains filling
- 11.Horizontal floor heightening
- 12.Water tank and fuel tank building
- 13.Platform filling and mending
- 14.Garden and rockeries
- 15.Foam concrete block
- 16.Foamed concrete precasting ,hollow wallboard casting

Features

1. The foam blending fast, blowing foam uniformly.
2. Without suspended matter, without the declining, it's good for steady pouring.
3. Little loss ratio of foam maintain the foam proportion in the foam concrete to make the products with stability density.
4. No dead angle design, mixing the material toughly, storage in its bottom is less than 10mm, no material left on the four walls internal the mixing drum.
5. It could mixing variable materials, such as cement, fly ash, sand pulp, sand stone, perlite, and slag etc.
6. Variable speed mixing and internal structure alteration make its installation easy and mixing frequency high, it saves energy.

Technical data:

Model	LD2000
Production Capacity	15-20 m ³ /h
Output Volume	1500 L
Material Input Volume	2000 L
Main Shaft Revolution	32 r/min
Hopper Lifting speed	22 m/min
Mixing Motor	11 kW
Winding Motor	5.5 kW
Water Pump Motor	1.1 kW
Vibrating Motor	0.55 kW
Foaming System	5.5 kW
Max. Moving Speed	15 km/h
Total Weight	3200 kg
Overall Dimension	2600x2250x3000 mm



郑州佰利得机器制造有限公司

Zhengzhou Lead Equipment Co., Ltd.

地址 ADD: 郑州市中原区西流湖街道办事处铁炉村西四环东 邮编 P.C.:450042
Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,
Zhongyuan District, Zhengzhou, Henan

网址 (Web): <http://www.leadcrete.com> E-Mail: sales@leadcrete.com

电话 TEL: +86-371-63902781 传真 FAX: +86-371-63526676

Zhengzhou Lead Equipment Co., Ltd.

Add: Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,
Zhongyuan District, Zhengzhou, Henan

Web: <http://www.leadcrete.com> E-Mail: sales@leadcrete.com

TEL: +86-371-63902781 FAX: +86-371-63526676