

Zhengzhou Lead Equipment Co., Ltd.

邮编 P.C.:450042

地址 ADD: 郑州市中原区西流湖街道办事处铁炉村西四环东 . Xisihuan Ring-Road East, Tielu,Xiliu lake sub-district, Zhongyuan District, Zhengzhou,Henan 网址(Web):http://www.leadcrete.com E-Mail: sales@leadcrete.com 电话 TEL: +86-371-63902781 传真 FAX:+86-371-63526676

## LGP400700100PL-D Cement grout plant for sale



The LGP400/700/100PL-D grout station is combination of mixer, agitator and hydraulic plunger grout pump in one plant. Mainly suitable for mixing and pumping water, cement, sand, bentonite, filler, clay power, silicates and other additives.

## **Cement grout plant application:**

1. Civil Engineering - dam foundations, tunnels, mining, soil nails, tiebacks, earth anchors, cable and rock bolts

2. Structural – building and bridge restoration, foundation stabilization, foundation raising, soil compaction grouting, soil & rock grouting

- 3. Construction pavement under sealing, slab jacking and slab raising
- 4. Marine underwater foundations, piers, breakers, shoreline foundations
- 5. Mining tunnel lining, contact grouting, shaft waterproofing
- 6. Utilities encasements, waterproofing, slope line grouting



Zhengzhou Lead Equipment Co., Ltd.

邮编 P.C.:450042

地址 ADD:郑州市中原区西流湖街道办事处铁炉村西四环东 . Xisihuan Ring-Road East, Tielu,Xiliu lake sub-district, Zhongyuan District, Zhengzhou,Henan 网址(Web):http://www.leadcrete.com E-Mail: sales@leadcrete.com 电话 TEL:+86-371-63902781 传真 FAX:+86-371-63526676

7. Geotechnical - deep well casing, monitor wells, well sealing and abandonment

## China cement grout plant feature:

1. Compact size, It is combination of mixer, agitator and hydraulic plunger grout pump in one base frame;

- 2. Have low pressure and high pressure, stepless speed regulation;
- 3. Yuken relief valve and directional valve for hydraulic system of grout pump;
- 4. Butterfly valve of mixer and agitator;

5. Oil temperature gauge can automatically control cooler fan working in normal temperature range, if temperature is too high, the machine will stop work automatically;

- 6. Full hydraulic drive, diesel engine;
- 7. Operation and maintenance are simple;
- 8. With ISO, CE certificate.

Ittimital Data.	
Туре	LGP400/700/100PL-D Grout Station
Diesel engine	25kw/36HP
Rotating speed of engine	2200r/min
Dimensions	2900*1900*1750mm
Weight	1900kg
	Mixer
Capacity	400L
W/C ratio	0.5-1
Rated Rev.	1500rpm
Agitator	
Volume	700L
Rated Rev.	36rpm
	Pump
Туре	Hydraulic Plunger pump
Pressure and Output	25 Bar (low pressure) 100L/min
	50 Bar (high pressure) 40L/min

## **Technical Data:**