

Double Acting Hollow Plunger Hydraulic Jack



Description

Double acting hollow plunger hydraulic jack has all the functions of a general hydraulic jack, can highly improve the convenience and double acting hollow plunger hydraulic jack also has the function of pulling. It also is used for tension PC strands, steel wire, axle and drill rod.

We are Double acting hollow plunger hydraulic jack supplier and manufacturer, our double acting hollow plunger hydraulic jack for sale around the world, and applied many in large projects, the effect is significant and very durable.

Application

Double acting hollow plunger hydraulic jack is very durable and long life, easy to operate and control, especially suitable for some larger projects. Double acting hollow plunger hydraulic jack can be used for lifting heavy machinery, bridge engineering, hydraulic engineering, port construction and other equipment.

According requirements we can customize hydraulic jack for our customers.

1. Double acting hollow plunger hydraulic jack can be used widely in post-tensioning operation for prestressed concrete bridges, foundation anchorage, immense constructions, ground anchorage, marine constructions, etc. projects.
2. Hollow plunger hydraulic jack for post tension is mainly used in to tensioning the PC strands/steel wire of the bridge construction.
3. With double acting hollow hydraulic jack together use the complete set: anchorage, electric oil pump, mixer, grouting pump machine, push machine for PC strand/ steel wire.
4. General tonnage of the hollow hydraulic jacks is based on the anchor's holes to match use.



郑州佰利得机器制造有限公司

Zhengzhou Lead Equipment Co., Ltd.

地址 ADD: 郑州市中原区西流湖街道办事处铁炉村西四环东
Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,
Zhongyuan District, Zhengzhou, Henan

邮编 P.C.:450042

网址 (Web): <http://www.leadcrete.com> E-Mail: sales@leadcrete.com

电话 TEL: +86-371-63902781 传真 FAX: +86-371-63526676

Features

1. Double acting hollow plunger hydraulic jack version for fast retraction.
2. Double acting hydraulic jack design can highly improve the convenience.
3. Baked enamel finish for increasing corrosion resistance.
4. Hollow hydraulic jack for sale is used for tension PC strands, steel wire, axle and drill rod.
5. Built in safe valve can protect hydraulic jack when over loading.
6. Plunger wiper reduces contamination, extending cylinder life.
7. High pressure hydraulic jack is very durable in large projects.
8. Double acting hollow hydraulic jack cylinder can bear Max loading when Max stroke.
9. Interchangeable, hardened grooved saddles are standard.
10. High quality seal ring makes the hollow hydraulic cylinder's life more long, with no oil leakage.
11. Double acting hydraulic cylinder is easily operated and control.
12. Leadcrete can design hydraulic jacks in accordance with demands of customers.
13. Double acting plunger hydraulic jack allows for both pull and push forces.
14. Double acting hollow hydraulic jack for sale is safety valve in retract side of cylinder helps to prevent damage over-pressurization.





郑州佰利得机器制造有限公司

Zhengzhou Lead Equipment Co., Ltd.

地址 ADD: 郑州市中原区西流湖街道办事处铁炉村西四环东 邮编 P.C.:450042
Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,
Zhongyuan District, Zhengzhou, Henan

网址 (Web): <http://www.leadcrete.com> E-Mail: sales@leadcrete.com

电话 TEL: +86-371-63902781 传真 FAX: +86-371-63526676

Technical data

Model	Capacity (T)	Stroke B-A (mm)	Own body height	Extend height	Outer diameter (mm)	Center hole (mm)	Weight (Kg)
			A (mm)	B (mm)			
RRH-307	30	178	330	508	114	33.3	22
RRH-3010		257	432	689	114	33.3	27
RRH-603	60	89	248	337	159	53.8	28
RRH-606		165	324	489	159	53.8	35
RRH-6010		257	438	695	159	53.8	46
RRH-1001	100	38	165	203	213	79.2	39
RRH-1003		76	254	330	213	79.2	61
RRH-1006		152	342	495	213	79.2	79
RRH-10010		257	460	718	213	79.2	107
RRH-1508	150	203	349	552	248	79.5	111

Zhengzhou Lead Equipment Co., Ltd.

Add: Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,
Zhongyuan District, Zhengzhou, Henan

Web: <http://www.leadcrete.com> E-Mail: sales@leadcrete.com

TEL: +86-371-63902781 FAX: +86-371-63526676