

郑州佰利得机器制造有限公司

Zhengzhou Lead Equipment Co., Ltd.

地址 ADD: 郑州市中原区西流湖街道办事处铁炉村西四环东

邮编 P.C.:450042

Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,

Zhongyuan District, Zhengzhou, Henan

电话 TEL: +86-371-63902781 传真 FAX:+86-371-63526676

Wedges And Anchor for Prestressed Strand



Description

Wedges and anchor for prestressed strand systems

- 1. Wedges and anchor for prestressed strand has high performance with good quality
- 2. Wedges and anchor for prestressed strand used for railway, bridge highway. buildings
- 3. Flat or slab anchor systems

Application

Wedges and anchor for prestressed strand have been widely adopted by modern construction, especially used in pre-tension or post-tension for concrete constructions as building materials, such as bridge construction, railway, and highway construction, buildings and channel construction, etc.

Features

- 1. LBM15(13) flat stressing-end anchorage is used for the strand with a diameter of 15.2-12.7, 12.7-12.9.
- 2. If the prestressing strand is collocated in plate-type, you can arrange the prestressing strand into a flat redial pattern by flat anchorage to avoiding to increasing the thickness of plating.
- 3. Anchor for prestressed strand includes flat anchor plate, working wedge, flat bearing plate, and uses the QYC front-end fixed jack to stressing.
- 5. Wedges and anchors for prestressed strand can work automatically, have a high anchor efficiency and very good performance. They are easy to use, safe and reliable. They are the crystallization of large quantity of experiences and scientific research.
- 6. They are used to anchor prestressing strands from 12.7mm and 15.2mm, 15.24mm.varies from 1 to 22 and we can produce according to your specific requirements.
- 7. The strength of the extension of a single can be up to 2000 Mpa.



郑州佰利得机器制造有限公司

Zhengzhou Lead Equipment Co., Ltd.

地址 ADD: 郑州市中原区西流湖街道办事处铁炉村西四环东

邮编 P.C.:450042

Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,

Zhongyuan District, Zhengzhou, Henan

电话 TEL: +86-371-63902781 传真 FAX:+86-371-63526676

Technical data

Model	flat anchor plate		flat bellows		flat base plate			flat spiral spring			
	Α	В	С	D	E	F	L	G	Н	N	Т
LBM15(13)-2	80	46	52	22	160	70	140	160	100	5	45
LBM15(13)-3	115	46	65	22	180	70	150	180	100	5	45
LBM15(13)-4	150	46	74	22	220	80	210	220	100	5	45
LBM15(13)-5	185	46	90	22	260	80	270	260	100	5	45





Zhengzhou Lead Equipment Co., Ltd.

Add: Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,

Zhongyuan District, Zhengzhou,Henan

Web: http://www.leadcrete.com E-Mail: sales@leadcrete.com

TEL: +86-371-63902781 FAX:+86-371-63526676