

Single Acting Hydraulic Cylinder Price



Description

Single acting hydraulic cylinder has safe protect pressurizer, built-in pressure relief valve in order to protect overloading, and it is good for safe operate. All the model can be customized according to client's requirements, single acting hydraulic cylinder price is different for different models, Single acting hydraulic cylinder price is reasonable and stable performance, it is mainly used for electric power, building, machine manufacturer, mining, subway, bridge and shipbuilding and kinds of industry for installing, lifting and tear down.

Application

Single acting hydraulic cylinder price is reasonable, stable performance, long life, Single acting hydraulic cylinder is mainly used in power, construction, machinery manufacturing, mining, subway, bridge and shipbuilding and various industries for installation, lifting and disassembly; shipbuilding, metallurgy, petrochemical, railway Lifting, stretching, pressing and other operations in engineering and other industries.

Features

- 1) Single acting hydraulic cylinder has single acting design, spring rebound.
- 2) Single acting hydraulic cylinder uses stoving varnish has more better anti-corrosion.
- 3) Dustband of single acting hydraulic cylinder can reduce pollution, it can extend hydraulic cylinder's usage life.
- 4) Single acting hydraulic cylinder is mainly used for power supply, construction, manufacturing, mining, railway bridges, ships, etc.



郑州佰利得机器制造有限公司

Zhengzhou Lead Equipment Co., Ltd.

地址 ADD: 郑州市中原区西流湖街道办事处铁炉村西四环东 邮编 P.C.:450042
 Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,
 Zhongyuan District, Zhengzhou, Henan

网址 (Web): <http://www.leadcrete.com> E-Mail: sales@leadcrete.com

电话 TEL: +86-371-63902781 传真 FAX: +86-371-63526676



Technical data

Model	Tonnage	Stroke	Own body height	Extend height	Efficiency area	Capacity of hydraulic oil	Outer diameter	Weight
	T	mm	mm	mm	Of cylinder cm ²	cm ³	mm	Kg
RC-50	5	16	41	57	6.4	10	55	1
RC-51		25	90	115	6.4	16	55	1
RC-53		76	145	221	6.4	49	55	1.5
RC-55		127	196	323	6.4	81	55	1.9
RC-57		178	253	431	6.4	114	55	2.4
RC-59		232	304	536	6.4	148	55	2.8
RC-101	10	25	80	105	14.4	36	60	1.8
RC-102		54	111	165	14.4	78	60	2.3
RC-104		105	161	266	14.4	151	60	3.3
RC-106		156	238	394	14.4	225	60	4.4
RC-108		203	288	491	14.4	292	60	5.4
RC-1010		257	339	596	14.4	370	60	6.4
RC-1012		305	390	695	14.4	439	60	6.8



郑州佰利得机器制造有限公司

Zhengzhou Lead Equipment Co., Ltd.

地址 ADD: 郑州市中原区西流湖街道办事处铁炉村西四环东 邮编 P.C.:450042
 Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,
 Zhongyuan District, Zhengzhou, Henan

网址 (Web): <http://www.leadcrete.com> E-Mail: sales@leadcrete.com

电话 TEL: +86-371-63902781 传真 FAX: +86-371-63526676

RC-1014		356	441	797	14.4	513	60	8.2
RC-151	15	25	104	129	20.3	51	70	3.3
RC-152		51	129	180	20.3	104	70	4.1
RC-154		102	180	282	20.3	207	70	5
RC-156		152	252	404	20.3	309	70	6.8
RC-158		203	302	505	20.3	412	70	8.2
RC-1510		254	353	607	20.3	516	70	9.5
RC-1512		305	404	709	20.3	619	70	10.9
RC-1514		356	455	811	20.3	723	70	11.8
RC-251	25	25	120	145	33.2	83	90	5.9
RC-252		51	145	196	33.2	169	90	6.4
RC-254		102	196	298	33.2	339	90	8.2
RC-256		159	253	412	33.2	528	90	10
RC-258		210	304	514	33.2	697	90	12.3
RC-2510		260	355	615	33.2	863	90	14.1
RC-2512		311	405	716	33.2	1033	90	16.3
RC-2514		362	456	818	33.2	1202	90	17.1
RC-308	30	210	337	547	41.9	880	102	18.1
RC-502	50	51	136	19%	71.3	364	127	15
RC-504		102	19%	289	71.3	727	127	19.1
RC-506		159	243	402	71.3	1134	127	23.2
RC-5013		337	421	758	71.3	2403	127	37.7
RC-756	75	156	246	402	102.6	1601	160	29.5
RC-7513		334	452	786	102.6	3427	160	59
RC-1006	100	168	267	435	133.2	2238	180	59
RC-10010		260	359	619	133.2	3463	180	72.6

Zhengzhou Lead Equipment Co., Ltd.

Add: Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,
 Zhongyuan District, Zhengzhou, Henan

Web: <http://www.leadcrete.com> E-Mail: sales@leadcrete.com

TEL: +86-371-63902781 FAX: +86-371-63526676