



LSZ3000V Guniting Machine Price

LSZ3000V Guniting Machine with variable output is an updated version, based on the popular equipment in China. And it mainly is used for dry/wet spraying concrete. With comparing the popular equipment, its advantages are easy sealing, smooth stream and uniform spraying. It also has some obvious advantages such as advanced technology, Perfect structure, stable performance, convenient operation and longevity of service etc. It is widely employed in mining, tunnel, culvert, subway, hydropower engineering, underground excavation engineering etc.



Certificates:



Technical Data:

Rated output	2-5m ³ /h
Max. horizontal conveying distance	35m(wet) 200m(dry)
Max. aggregate size	Φ 15mm
Concrete slump	8~15cm(wet)
Conveying hose	Φ 50/65mm
Operating air pressure	0.2~0.6MPa
Air consumption	10~12m ³ /min
Rotor Rev.	5-12r/min
Rebound	≤10 %
Main electric motor power	7.5kW
Variable gearbox:	MBLY75
Overall dimension (L×W×H)	1580×850×1250mm
Weight	950Kg

A complete set of LSZ3000V Gunit Shortcorte Machine:

No.	Description	Quantity	Unit	Remarks
1	Main Machine	1	set	
2	Nozzle Assy.	1	set	
3	Conveying Hose, ID64mm, 50ft.Length	1	piece	
4	Rubber Hose Joint	3	piece	Fitting
5	Quick Coupling	3	piece	
6	Upper Sealing Plate	1	piece	
7	Lower Sealing Plate	1	piece	
8	Dosing pump tube	1	piece	

Picture of various parts:



LEC Motor support global service:



Pictures from several angles:



郑州佰利得机器制造有限公司

Lead Equipment Co.,Ltd.

Web: www.leadcrete.cn

Add: Xisihuan Ring-Road East,
Tielu, Xiliu lake sub-district,
Zhongyuan District, Zhengzhou, Henan

P.C. 450042

Tel: +86-371-63902781

Fax: +86-371-63526676

Email: sales@leadcrete.com