

### LZ-3 Gunite Spraying Machine Manufacturer

### 1. LZ-3 gunite spraying machine description:

LZ-3 gunite spraying machine is small-sized shotcrete machine for the dry spraying process.

LZ-3 gunite spraying machine can be used as well for small jobs, such as joint filling, swimming pool, refractory application and extensive slope consolidation work, etc. LZ-3 gunite spraying machine is available in following versions:

Basic: electric drive can be combined with tyre chassis

Extended (optional): air motor or diesel drive combined skid or rail-wheel

### 2. LZ-3 gunite spraying machine technical parameters:

#### **Electric Motor Driven**

Output Capacity	$3m^3/h$		
Max. Horizontal Conveying Distance	200m		
Suitable Mix Ratio(Cement/Sand)	≤1:3~5		
Max. Aggregate Size	Ф10 mm		
Conveying Hose Inner Diameter	Ф38/Ф50mm		
Conveying Pressure	0.2-0.4MPa(29-58PSI)		
Air Consumption for conveying material	5~6m <sup>3</sup> /min(180-215CFM)		
Material Charging Height	0.9m		
Rotor Speed	14r/min		
Motor Power	3kW(4hp),IP55		
Available Voltage	220V,380V, 440V,660V 50Hz/60Hz		
Overall Dimension(length×width×height)	1.13×0.54×1.02m		
Net Weight	430kg		

#### **Air Motor Driven**

Output Capacity	$1.5-3m^3/h$		
Max. Horizontal Conveying Distance	200m		
Suitable Mix Ratio(Cement/Sand)	≤1:3~5		
Max. Aggregate Size	Ф10 mm		
Conveying Hose Inner Diameter	Ф50mm		
Conveying Pressure	0.2-0.4MPa(29-58PSI)		
Air Consumption for conveying material	5~6m <sup>3</sup> /min(180-215CFM)		
Air Motor Air Pressure	0.5MPa(71PSI)		
Material Charging Height	0.9m		
Rotor Speed	14r/min		

Version: Aug.2012 Copyright@LEAD Equipment Co., Ltd.

Air Motor Type	TMH3.2	
Air Motor Air Consumption	4.8m <sup>3</sup> /min(171CFM)	
Overall Dimension(length×width×height)	1.13×0.54×1.02m	
Net Weight	430kg(947lbs)	

#### Diesel driven:

Rated Output	2-3m 3 /h		
Max. Horizontal Conveying Distance	200m		
Suitable Mix Ratio(Cement/Sand)	≤ 1: 3~5		
Max. Aggregate Size	Φ 10 mm		
Conveying Hose Inner Diameter	38/51mm		
Operating air Pressure	0.2-0.4MPa(29-58PSI)		
Air Consumption	5~6m 3 /min(180-215CFM		
Diesel Engine	10hp,2200rpm		
Diesel Engine Starting	Electric start		
Clutch Type in Diesel Engine	Automatic Clutch		
Material Charging Height	0.9m		
Rotor Speed	9-13r/min		
Overall Dimension(L× W× H)	1.8× 0.8× 1.2m		
Net Weight	480kg		

### **Certificate:**

CE AND ISO9001-2008





## A complete set of LZ-3 gunite spraying machine:

No.	Description	Quantity	Unit	Remarks
1	LZ-3 Main Machine	1	set	
2	Nozzle Assy.	1	set	
3	Conveying Hose, ID38mm, 50ft.Length	1	piece	
4	Water hose with hose hoop	1	piece	
5	Rubber Hose Joint(long)	1	piece	Fitting
6	Rubber Hose Joint(short)	2	piece	Fitting
7	Quick Coupling	3	piece	
8	Upper Sealing Plate	1	piece	
9	Lower Sealing Plate	1	piece	

## **Picture:**

## **Electric drive:**



Version: Aug.2012 Copyright@LEAD Equipment Co., Ltd.

### Air motor drive:





# **Application:**





Zhengzhou Lead Equipment Co., Ltd.

Add: Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,

Zhongyuan District, Zhengzhou, Henan

Web:http://www.leadcrete.com E-Mail: sales@leadcrete.com

TEL: +86-371-63902781 FAX:+86-371-63526676